



JRG LegioStop Verteilbatterie komplett Rotguss - neu

- Temperatur: max. 30°C
 - Werkstoff: Rotguss, Edelstahl, EPDM, Kunststoff
 - Anschluss: Aussengewinde
 - Bestehend aus: JRGUSIT NG Batterieventil 5151, JRGURED Combi 1353, Muffenverschraubung 5178, Passstück 1135, JRGUSIT Combi Verteilarmatur 5191
 - Auslieferungszustand: Druckminderer 400 kPa (4 bar) Einstellbereich 200 - 600 kPa (2 - 6 bar), Sicherheitsventil 600 kPa (6 bar)
- **Verfügbar ab Mitte September 2024

	DN (mm)	Zoll (inch)	DN-DN-DN-DN (mm)	JRG NPK Code	GF NPK Code	SP	Gewicht (kg)
**	25	1	25-20-25-25	1532.400	355 623 575		9.700
**	32	1 ¼	32-20-25-25	1532.480	355 623 574		9.700

	DN (mm)	Zoll (inch)	DN-DN-DN-DN (mm)	d1 G (inch)	d2 G (inch)	d3 G (inch)	d4 G (inch)	d5 Rp (inch)	d6 Rp (inch)	d7 G (inch)	d8 G (inch)	d9 G (inch)
**	25	1	25-20-25-25	1 ¼	1	1 ¼	¾	¾	¼	¾	1	½
**	32	1 ¼	32-20-25-25	1 ½	1	1 ¼	¾	¾	¼	¾	1	½

	DN (mm)	Zoll (inch)	DN-DN-DN-DN (mm)	d10 (mm)	h1 (mm)	h2 (mm)	h3 (mm)	h4 (mm)	l (mm)	l1 (mm)	l2 (mm)	l3 (mm)
**	25	1	25-20-25-25	TR 30 x 1.5	55	77	404	90	721	37	133	228
**	32	1 ¼	32-20-25-25	TR 30 x 1.5	56	77	403	109	775	42	149	261

	DN (mm)	Zoll (inch)	DN-DN-DN-DN (mm)	l4 (mm)	l5 (mm)	l6 (mm)	PN (bar)
**	25	1	25-20-25-25	145	130	48	16
**	32	1 ¼	32-20-25-25	145	130	48	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>