



JRG Auslaufventil Rotguss

- Werkstoff: Rotguss, Chromnickelstahl, EPDM, Metall
- Bestehend aus: integriertem Rohrbelüfter, Knebelgriff, Ventilsitz aus Chromnickelstahl
- Thread type d1 = R
- Gewindetyp d2 = G
- Gewindetyp d3 = G
- *verchromt

DN (mm)	GN (inch)	Zoll (inch)	JRG Code	NPK	GF Code	NPK	SP	Gewicht (kg)
15	½	½	7016.240		355 624 419	633 123	1	0.525
20	¾	¾	7016.320		355 624 434	633 124	1	0.001
* 15	½	½	7016.241		355 624 423	633 133	1	0.540
* 20	¾	¾	7016.321		355 624 438	633 134	1	0.565

DN (mm)	d1 (inch)	d2 (inch)	d3 (inch)	d4 (mm)	h1 (mm)	h2 (mm)	l1 (mm)	l2 (mm)	PN (bar)	⬡ (mm)	⬢ (mm)
15	½	¾	½	45	76	36	22	94	16	28	6
20	¾	1	½	45	76	39	25	93	16	28	6
* 15	½	¾	½	45	76	36	22	94	16	28	6
* 20	¾	1	½	45	76	39	25	93	16	28	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>