



JRG LegioStop Verteilbatterie komplett Rotguss - neu

- Temperatur: max. 30°C
- Werkstoff: Rotguss, Edelstahl, EPDM, Kunststoff
- Auslieferungszustand: Druckminderer 400 kPa (4 bar) Einstellbereich 200 - 600 kPa (2 - 6 bar), Sicherheitsventil 600 kPa (6 bar)
- Anschluss: Aussengewinde
- Bestehend aus: JRGUSIT NG Batterieventil 5151, JRGURED 1303, JRGUSIT Combi Verteilarmatur 5191
- Gewindetyp d1 = G
- Gewindetyp d2 = G
- Gewindetyp d3 = G
- Thread type d4 = Rp
- Thread type d5 = Rp
- Thread type d6 = Rp
- Thread type d7 = G
- Thread type d8 = G
- Thread type d9 = G

DN (mm)	Zoll (inch)	JRG Code	NPK	GF Code	NPK	SP	Gewicht (kg)
25	1	1511.400		355 623 519	628 475	1	5.705
32	1 1/4	1511.480		355 623 529	628 476	1	5.863

d1 (inch)	d2 (inch)	d3 (inch)	d4 (inch)	d5 (inch)	d6 (inch)	d7 (inch)	d8 (inch)	d9 (inch)	d10 (mm)	h1 (mm)	h2 (mm)	h3 (mm)	h4 (mm)	l (mm)
1 1/4	1	1 1/4	3/4	3/4	1/4	3/4	1	1/2	TR 30 x 1.5	55	77	55	90	586
1 1/2	1	1 1/4	3/4	3/4	1/4	3/4	1	1/2	TR 30 x 1.5	56	77	67	109	618

l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	l5 (mm)	l6 (mm)	PN (bar)
37	133	93	145	130	48	16
42	149	104	145	130	48	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>