



## JRG LegioStop Batterie de distribution complète bronze - nouveau

- Température: max. 30°C
- Matériau: bronze, acier inoxydable, EPDM, matière synthétique
- Réglage d'usine: réducteur de pression 400 kPa (4 bar) réglable 200 - 600 kPa (2 - 6 bar), soupape de sûreté 600 kPa (6 bar)
- Raccord: filetage mâle
- Comprendant: JRGUSIT NG robinet de distribution 5151, JRGURED 1303, JRGUSIT Combi batterie de distribution 5191
- Thread type d1 = G
- Type de filetage d2 = G
- Type de filetage d3 = G
- Thread type d4 = Rp
- Thread type d5 = Rp
- Thread type d6 = Rp
- Thread type d7 = G
- Thread type d8 = G
- Thread type d9 = G

| DN   | Pouces | JRG CAN  | GF          | CAN     | SP | Poids |
|------|--------|----------|-------------|---------|----|-------|
| (mm) | (inch) | Code     | Code        |         |    | (kg)  |
| 25   | 1      | 1511.400 | 355 623 519 | 628 475 | 1  | 5.705 |
| 32   | 1 ¼    | 1511.480 | 355 623 529 | 628 476 | 1  | 5.863 |

| d1     | d2     | d3     | d4     | d5     | d6     | d7     | d8     | d9     | d10         | h1   | h2   | h3   | h4   | l    |
|--------|--------|--------|--------|--------|--------|--------|--------|--------|-------------|------|------|------|------|------|
| (inch) | (inch) | (inch) | (inch) | (inch) | (inch) | (inch) | (inch) | (inch) |             | (mm) | (mm) | (mm) | (mm) | (mm) |
| 1 ¼    | 1      | 1 ¼    | ¾      | ¾      | ¾      | ¾      | 1      | ½      | TR 30 x 1.5 | 55   | 77   | 55   | 90   | 586  |
| 1 ½    | 1      | 1 ¼    | ¾      | ¾      | ¾      | ¾      | 1      | ½      | TR 30 x 1.5 | 56   | 77   | 67   | 109  | 618  |

| l1   | l2   | l3   | l4   | l5   | l6   | PN    |
|------|------|------|------|------|------|-------|
| (mm) | (mm) | (mm) | (mm) | (mm) | (mm) | (bar) |
| 37   | 133  | 93   | 145  | 130  | 48   | 16    |
| 42   | 149  | 104  | 145  | 130  | 48   | 16    |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>