



JRG LegioStop Batteria di distribuzione completa bronzo - nuovo

- Temperatura: max. 30°C
- Materiale: bronzo, acciaio inossidabile, EPDM, plastica
- Regolazione di fabbrica: riduttore di pressione 400 kPa (4 bar) regolabile 200 - 600 kPa (2 - 6 bar), valvola di sicurezza 600 kPa (6 bar)
- Attacco: filetto maschio
- Composta di: rubinetto da batteria JRGUSIT NG 5151, JRGURED 1303, valvola di distribuzione JRGUSIT Combi 5191.
- Thread type d1 = G
- Tipo di filettatura d2 = G
- Thread type d3 = G
- Thread type d4 = Rp
- Thread type d5 = Rp
- Thread type d6 = Rp
- Thread type d7 = G
- Thread type d8 = G
- Thread type d9 = G

DN (mm)	Size (inch)	JRG code	NPK	GF code	NPK	SP	peso (kg)
25	1	1511.400		355 623 519	628 475	1	5.705
32	1 1/4	1511.480		355 623 529	628 476	1	5.863

d1 (inch)	d2 (inch)	d3 (inch)	d4 (inch)	d5 (inch)	d6 (inch)	d7 (inch)	d8 (inch)	d9 (inch)	d10	h1 (mm)	h2 (mm)	h3 (mm)	h4 (mm)	l (mm)
1 1/4	1	1 1/4	3/4	3/4	1/4	3/4	1	1/2	TR 30 x 1.5	55	77	55	90	586
1 1/2	1	1 1/4	3/4	3/4	1/4	3/4	1	1/2	TR 30 x 1.5	56	77	67	109	618

l1 (mm)	l2 (mm)	l3 (mm)	l4 (mm)	l5 (mm)	l6 (mm)	PN (bar)
37	133	93	145	130	48	16
42	149	104	145	130	48	16

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>