



JRGURED Druckminderer Rotguss - neu

- Temperatur: max. 30°C
- Werkstoff: Rotguss, Edelstahl, EPDM, Kunststoff
- Auslieferungszustand: 400 kPa (4 bar)
- Sekundärdruck: 200 - 600 kPa (2 - 6 bar)
- Anschluss: Manometer
- Gewindetyp d2 = G
- Gewindetyp d3 = Rp

DN (mm)	GN (inch)	Zoll (inch)	JRG Code	NPK	GF Code	NPK	SP	Gewicht (kg)
15	½	½	1303.015		350 740 101	613 153	1	0.600
20	¾	¾	1303.020		350 740 201	613 154	1	0.700
25	1	1	1303.025		350 740 301	613 155	1	1.300
32	1 ¼	1 ¼	1303.032		350 740 401	613 156	1	1.800
40	1 ½	1 ½	1303.040		350 740 501	613 157	1	3.400
50	2	2	1303.050		350 740 601		1	4.900
65	2 ½	2 ½	1303.065		350 740 701	613 161	1	5.015

DN (mm)	GN (inch)	d2 (inch)	d3 (inch)	d4 (mm)	h1 (mm)	h2 (mm)	l1 (mm)	z (mm)	⊕ (mm)	PN (bar)
15	½	¾	⅝	53	34	79	80	40	5	25
20	¾	1	⅝	53	42	81	85	43	5	25
25	1	1 ¼	⅝	60	55	90	100	50	5	25
32	1 ¼	1 ½	⅝	72	67	109	120	60	6	25
40	1 ½	1 ¾	⅝	80	80	122	145	73	6	25
50	2	2 ¾	⅝	96	98	151	175	88	8	25
65	2 ½	3	⅝	96	98	151	180	90	8	25

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>